

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Tractor, Vineyard Harvester

Version	SPECIAL
Type	TL
Tyre Size	540/65 R 28
LI/SS	149 D/152 A8

Dimensions International Standard

Section Width (mm)	530
Overall Diameter (mm)	1413
Static Loaded Radius (mm)	643
Rolling Circumference (mm)	4253
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E4-106R-000650
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1560	1820	2050	2275	2505	2700	2990	3250
50	1640	1915	2155	2395	2630	2835	3145	3415
40	1705	1990	2240	2485	2735	2950	3270	3550
30	1800	2095	2360	2620	2880	3105	3445	3740
10 LT	2095	2440	2745	3050	3355	3615	4010	4355
10 HT	1800	2095	2360	2620	2880	3105	3445	3740

Printed on 27/01/2021 07:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..