

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

US Standard

Construction

RADIAL

Machinery

Agriculture: Tractor, Vineyard Harvester

Version	SPECIAL
Type	TL
Tyre Size	540/65 R 30
LI/SS	150 D/153 A8

Dimensions US Standard

Usa code	94056934
Section Width (inch)	20.9
Overall Diameter (inch)	57.6
Static Loaded Radius (inch)	26.4
Rolling Circumference (inch)	173.3
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E4-106R-000651
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	3550	4140	4660	5170	5690	6140	6800	7400
30	3730	4350	4890	5430	5990	6450	7140	7760
25	3870	4510	5070	5630	6210	6680	7410	8050
20	4090	4760	5360	5950	6550	7050	7830	8500
5 LT	4760	5540	6240	6930	7630	8220	9120	9900
5 HT	4090	4760	5360	5950	6550	7050	7830	8500

Printed on 30/09/2020 10:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..