AGRIMAX RT 855 - Technical Specifications

Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

US Standard

Construction

RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	340/85 R 28 (13.6 R 28)
LI/SS	127 A8/B

Dimensions US Standard

Usa code	94021611
Section Width (inch)	13.9
Overall Diameter (inch)	50.7
Static Loaded Radius (inch)	23.1
Rolling Circumference (inch)	153.1
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-000593
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2130	2470	2820	3160	3520	3860
25	2130	2470	2820	3160	3520	3860
20	2280	2650	3020	3390	3770	4130
5 LT	2840	3320	3780	4240	4710	5170
5 HT	2280	2650	3020	3390	3770	4130

Printed on 4/20/2024 3:06 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..