

## AGRIMAX V-FLECTO - Technical Specifications



### Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

### UM

US Standard

### Construction

RADIAL

### Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 750/70 R 44
LI/SS	186 D

### Dimensions US Standard

Usa code	94066926
Section Width (inch)	29.9
Overall Diameter (inch)	85.6
Static Loaded Radius (inch)	37.7
Rolling Circumference (inch)	253.9
Rim Rec	DW 25 B
Rim Alt	DW 24 B
ECE	E11-106R-006765
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	8960	10200	11820	13350	14870	16390	17920	19060
From 40 to 25	9840	11310	12890	14660	16340	18010	19690	20940
20	10040	11540	13250	14960	16670	18370	20080	21360
12	10240	11770	13510	15260	17000	18740	20480	21780
5	10840	12440	14290	16130	17980	19820	21660	23040
5 Cyc	13790	15840	18190	20520	22870	25220	27570	29320
5 HT	10040	11540	13250	14960	16670	18370	20080	21360

\* - For 10 Cyc application Inflation pressure to be Increased by 0.8 bar.

Printed on 13/05/2021 20:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..