

# AGRIMAXFACTOR - Technical Specifications

## Description



AGRIMAXFACTOR is BKT’s brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire’s braking results on wet surface are excellent.

In a nutshell, AGRIMAXFACTOR’s overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of e-vehicles’ battery packages. The exclusive sidewall shows the perfectly aligned “E-READY” logo that highlights BKT’s commitment to electric mobility.

<b>UM</b>	International Standard
<b>Construction</b>	RADIAL
<b>Machinery</b>	Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	710/70 R 42
LI/SS	173D/176A8

## Dimensions International Standard

Section Width (mm)	716
Overall Diameter (mm)	2061
Static Loaded Radius (mm)	935
Rolling Circumference (mm)	6198
SRI (mm)	975
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-007526
TRA Code	R1W

### Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	3055	3510	4030	4550	5070	5590	6110	6500
50	3210	3690	4235	4780	5325	5870	6420	6825
40	3340	3835	4405	4970	5540	6110	6675	7100
30	3515	4040	4635	5235	5835	6430	7030	7475
10 LT	4095	4705	5405	6100	6795	7495	8190	8710
10 HT	3515	4040	4635	5235	5835	6430	7030	7475

Printed on 26/11/2022 17:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..