

□

AS 505 - Technical Specifications

□ Description

AS 505 is best suited for soil tillage operations with trailers and implement machinery. It features excellent self-cleaning properties and increased traction on the ground, especially on muddy soil. The tire also ensures a long tire life-cycle.

UM

US Standard

Construction

BIAS

Machinery

- Agriculture: Implement Machinery, Trailer

- Version
STANDARD
- Type
TL
- Tyre Size
6.5/80 - 15
- LI/SS DRIVE WHEEL
86 A8
- LI/SS FREE ROLLING
98 A8

Dimensions US Standard

- Usa code
94019465
- Ply Rating
6
- Section Width (inch)
6.7
- Overall Diameter (inch)
26.9
- Static Loaded Radius (inch)
12.8
- Rolling Circumference (inch)
82.9
- Rim Rec
5.0
- Rim Alt
4½ K ; 5 K ; 5 J
- ECE
E4-106R-002188

Load capacity (lbs)

mph / psi 52

5 FR 2310

15 FR 1970

20 FR 1850

25 FR 1650

5 DW 1630

15 DW 1390

20 DW 1310

25 DW 1170

Printed on 05/07/2022 15:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..