

AW 726 - Data Sheet



Description

AW 726 has been specially designed for trailers in transport operations. It is best suited for both on-and-off-the-road usage. AW 726 shows excellent road performance and self-cleaning features. The block pattern design provides an extended tire life-cycle.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Trailer

SIZE	Version	USACode	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
11.5/80 - 15.3	ARAMID BELTED	94064366	126 A8	139 A8	14	9.00		11.8	33.7	14.3	99.6	TL	E11-106R-005264 E11-106R-006974
11.5/80 - 15.3	STANDARD	94053698	126 A8	139 A8	14	9.00		11.8	33.7	14.3	99.6	TL	
11.5/80 - 15.3	STEEL BELTED	94067695	126 A8	139 A8	14	9.00		11.8	33.7	14.7	100	TL	
400/60 - 15.5	STANDARD	94054008	137 A8	149 A8	18	AG 13.00		15.7	34.4	0	0	TL	
420/55 - 17	STANDARD	94055647	121 A8	133 A8		13.00		16.3	35	15.4	101.7	TL	

Printed on 19/10/2021 01:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..