

## CON STAR - Technical Specifications



### Description

CON STAR is particularly suitable for compact loaders and telehandlers in agro-industrial, lifting and loading applications. It features great traction along with excellent vertical and horizontal stability. CON STAR has been made of a cut-and-chip-resistant compound contributing to an extended tire life-cycle.

### UM

US Standard

### Construction

BIAS

### Machinery

Agriculture: Compact Loader, Telehandler  
Industrial: Compact Loader, Telehandler

Version	INDUSTRIAL
Type	TL
Tyre Size	340/80 - 20 (12.5/80 - 20)
LI/SS	144 A8

### Dimensions US Standard

Usa code	94051311
Section Width (inch)	13.8
Overall Diameter (inch)	41.9
Static Loaded Radius (inch)	19.3
Rolling Circumference (inch)	128.8
Rim Rec	11
Rim Alt	12 ; 11 SDC ; 12 SDC ; W 10 ; W 11
ECE	E11-106R-003021

### Load capacity (lbs)

mph / psi	58
25	6170

*All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*