

CON STAR - Technical Specifications



Description

CON STAR is particularly suitable for compact loaders and telehandlers in agro-industrial, lifting and loading applications. It features great traction along with excellent vertical and horizontal stability. CON STAR has been made of a cut-and-chip-resistant compound contributing to an extended tire life-cycle.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Compact Loader, Telehandler
Industrial: Compact Loader, Telehandler

Version	INDUSTRIAL
Type	TL
Tyre Size	400/70 - 24 (16.0/70 - 24)
LI/SS	158A8

Dimensions US Standard

Usa code	94051977
Section Width (inch)	15.6
Overall Diameter (inch)	46.3
Static Loaded Radius (inch)	21.4
Rolling Circumference (inch)	140
Rim Rec	13
Rim Alt	DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L
ECE	E11-106R-003025

Load capacity (lbs)

mph / psi	73
25	9370

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..