

CON STAR - Data Sheet



Description

CON STAR is particularly suitable for compact loaders and telehandlers in agro-industrial, lifting and loading applications. It features great traction along with excellent vertical and horizontal stability. CON STAR has been made of a cut-and-chip-resistant compound contributing to an extended tire life-cycle.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Compact Loader, Telehandler
Industrial: Compact Loader, Telehandler

| SIZE | Version | LI/SS | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|-------------------------------|------------|--------|----|---------|--|-----|------|-----|------|-----|------|-----------------|
| 340/80 - 18 (12.5/80 - 18) | INDUSTRIAL | 143 A8 | | 11 | 12 ; 11 SDC ; 12 SDC ; W 10 ; W 11 | 350 | 1015 | 460 | 3075 | 475 | TL | E11-106R-003020 |
| 340/80 - 20 (12.5/80 - 20) | INDUSTRIAL | 144 A8 | | 11 | 12 ; 11 SDC ; 12 SDC ; W 10 ; W 11 | 350 | 1065 | 491 | 3272 | 500 | TL | E11-106R-003021 |
| 380/75 - 20 (14.5 - 20) | INDUSTRIAL | 148 A8 | | W 12 | W 11 ; 12 SDC ; 12 ; W 13 ; 13 SDC ; 13 | 385 | 1080 | 500 | 3273 | | TL | E11-106R-003022 |
| 400/70 - 20 (16.0/70 - 20) | INDUSTRIAL | 149 A8 | 16 | 13 | 12 SDC ; 13 SDC ; 14 | 405 | 1080 | 501 | 3303 | 525 | TL | E11-106R-003024 |
| 400/70 - 20 (16.0/70 - 20) | INDUSTRIAL | 156 A8 | | 13 | 12 SDC ; 13 SDC ; 14 | 405 | 1080 | 501 | 3303 | 525 | TL | E11-106R-003023 |
| 400/70 - 24 (16.0/70 - 24) | INDUSTRIAL | 158 A8 | | 13 | DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L | 395 | 1175 | 544 | 3556 | 575 | TL | E11-106R-003025 |
| 400/80 - 24 (15.5/80 - 24) | INDUSTRIAL | 162 A8 | 20 | DW 13 | DW 12 ; DW 13 L ; DW 14 L | 405 | 1250 | 570 | 3781 | 600 | TL | E11-106R-003026 |
| 440/80 - 24 (17.0/80 - 24) | INDUSTRIAL | 168 A8 | 22 | DW 14 L | DW 13 ; DW 13 L ; DW 15 L | 455 | 1315 | 610 | 3986 | 625 | TL | E11-106R-003027 |
| 460/70 - 24 (17.5L - 24) | INDUSTRIAL | 159 A8 | | DW 15 L | DW 14 L ; DW 16 L | 460 | 1250 | 562 | 3784 | 600 | TL | E11-106R-003029 |
| 500/70 - 24 (19.5L - 24) | INDUSTRIAL | 164 A8 | | DW 16 L | DW 15 L ; DW 18 L | 505 | 1300 | 579 | 3926 | 625 | TL | E11-106R-003031 |
| 480/80 - 26 (18.4 - 26) | INDUSTRIAL | 160 A8 | | DW 15 L | DW 16 L | 490 | 1410 | 643 | 4272 | 675 | TL | E11-106R-003033 |
| 440/80 - 28 (16.9 - 28) | INDUSTRIAL | 156 A8 | | DW 14 L | DW 13 ; DW 13 L ; DW 15 L | 450 | 1420 | 632 | 4299 | 675 | TL | E11-106R-003035 |

Printed on 01/12/2022 05:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..