

## EARTHMAX SR 22 - Technical Specifications



### Description

EARTHMAX SR 22 (G-2/L-2) is an *All Steel* radial tire specially designed for motor graders and loaders operating in extreme winter conditions on ice or snow. Operators will appreciate both excellent traction and stability provided by the large and non-directional tread design.

### UM

International Standard

### Construction

RADIAL

### Machinery

Industrial: Dozer, Grader, Loader  
OTR: Dozer, Grader, Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	15.5 R 25
LI/SS	146 A8/169 A2

### Dimensions International Standard

Overall Width (mm)	385
Overall Diameter (mm)	1275
Static Loaded Radius (mm)	557
Rolling Circumference (mm)	3841
Rim Rec	12.00/1.3
Star Rating	*
TRA Code	G2/L2

### Load capacity (Kg)

km/h / bar	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00
40	1550	1750	2000	2180	2360	2575	2800	3000	-	-	-	-	-
10	-	-	-	-	-	-	-	-	5000	5150	5450	5600	5800

*publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*