

EARTHMAX SR 23 - Technical Specifications



Description

EARTHMAX SR 23 (G-2/L-2) is an All Steel radial tire specially designed for motor graders and loaders. It features superior forward and lateral traction as well as exceptional self-cleaning properties. The durable casing and the particularly cut-resistant tread provide a long service life.

UM

US Standard

Construction

RADIAL

Machinery

OTR: Grader, Loader

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 20.5 R 25 |
| LI/SS | 161 A8/186 A2 |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94060603 |
| Overall Width (inch) | 21.1 |
| Overall Diameter (inch) | 58.7 |
| Static Loaded Radius (inch) | 26.3 |
| Rolling Circumference (inch) | 176.7 |
| Rim Rec | 17.00/2.0 |
| Star Rating | * |
| TRA Code | G2/L2 |

Load capacity (lbs)

| mph / psi | 18 | 22 | 25 | 29 | 33 | 36 | 40 | 44 | 58 | 62 | 65 | 69 | 73 |
|-----------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 25 | 5360 | 6150 | 6950 | 7600 | 8550 | 9100 | 9650 | 10200 | -- | -- | -- | -- | -- |
| 5 | -- | -- | -- | -- | -- | -- | -- | -- | 17600 | 18200 | 19300 | 19800 | 20900 |

its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..