



EARTHMAX SR 23 - Data Sheet



Description

EARTHMAX SR 23 (G-2/L-2) is an All Steel radial tire specially designed for motor graders and loaders. It features superior forward and lateral traction as well as exceptional self-cleaning properties. The durable casing and the particularly cut-resistant tread provide a long service life.

UM

US Standard

Construction

RADIAL

Machinery

OTR: Grader, Loader

SIZE	Version	USACode	TRA Code	Star R	L/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
15.5 R 25	CUT RESISTANT COMPOUND	94046829	G2/L2	*	146 A8/169 A2	12.00/1.3		15.1	49.8	22	147.9	TL
17.5 R 25	CUT RESISTANT COMPOUND	94060313	G2/L2	*	153 A8/176 A2	14.00/1.5	14.00/1.3 (DC)	17.6	53	24.1	161.7	TL
20.5 R 25	CUT RESISTANT COMPOUND	94060603	G2/L2	*	161 A8/186 A2	17.00/2.0		21.1	58.7	26.3	176.7	TL

Printed on 03/12/2021 05:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..