

EARTHMAX SR 33 - Technical Specifications



Description

Earthmax SR 33 is a radial tire for multipurpose trucks. Its multi-block tread pattern has been specially designed to guarantee extraordinary traction on soft, sandy, or muddy surfaces. Earthmax SR 33 provides outstanding stability in addition to best self-cleaning properties. The strong All Steel casing features excellent durability and resistance to snag and punctures.

UM

US Standard

Construction

RADIAL

Machinery

Industrial: Universal Vehicle

| | |
|-----------|----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 365/80 R 20 (14.5 R 20) |
| LI/SS | 152 K |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94061907 |
| Overall Width (inch) | 14.2 |
| Overall Diameter (inch) | 43.1 |
| Static Loaded Radius (inch) | 19.5 |
| Rolling Circumference (inch) | 130.6 |
| Rim Rec | 11 |
| ECE | E11-54R-0017314 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 90 |
| 68 | 7850 |

publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..