



## ***EARTHMAX SR 423 - Data Sheet***



### *Description*

EARTHMAX SR 423 is an All Steel radial tire suitable for a variety of applications including quarry, haulage and logging operations. The non-directional tread pattern provides excellent traction and stability on any type of terrain. The tire is ideal for handling heavy loads. The strong *All Steel* casing features excellent wear and resistance to snag and punctures. Its reinforced bead and the shoulder design contribute to an extended tire life-cycle even under heavy-duty service conditions.

### *UM*

International Standard

### *Construction*

RADIAL

### *Machinery*

OTR: On/Off Truck

| SIZE                        | Version  | LI/SS     | RIM REC | RIM ALT | OW  | OD   | Type |
|-----------------------------|----------|-----------|---------|---------|-----|------|------|
| 10.00 R 20                  | STANDARD | 149/146 J | 7.50    | 8.00    | 270 | 1065 | TT   |
| 11.00 R 20                  | STANDARD | 152/149 J | 8.00    | 8.50    | 285 | 1100 | TT   |
| 12.00 R 20                  | STANDARD | 154/150 J | 8.50    | 9.00    | 302 | 1132 | TT   |
| 12.00 R 24<br>(325/95 R 24) | STANDARD | 160/156 K | 8.50    |         | 318 | 1243 | TT   |
| 325/95 R 24<br>(12.00 R 24) | STANDARD | 160/156 K | 8.50    |         | 318 | 1243 | TT   |

Printed on 03/10/2022 14:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..