

EARTHMAX SR 50 - Technical Specifications



Description

EARTHMAX SR 50 (L-5) is an *All Steel* radial tire specially designed for loaders. The durable casing and sidewall protectors are ideal for the most demanding operations. EARTHMAX SR 50 is made of a special cut-resistant compound which ensures a long wear life. Operators will also appreciate its excellent traction, stability and comfortable ride.

UM

US Standard

Construction

RADIAL

Machinery

OTR: Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	208 A2

Dimensions US Standard

Usa code	94037230
Overall Width (inch)	30.5
Overall Diameter (inch)	74.8
Static Loaded Radius (inch)	33.9
Rolling Circumference (inch)	225.3
Rim Rec	25.00/3.5
Rim Alt	25.00/3.5 IF
Star Rating	*
TRA Code	L5

Load capacity (lbs)

mph / psi	58	62	65	69	73
5	34200	35300	37500	38600	39700

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..