

## EARTHMAX SR 51 - Technical Specifications



**Description** EARTHMAX SR 51 (L-5) is an *All Steel* radial tire specially designed for loaders or dozers. EARTHMAX SR 51 is ideal for severe operations requiring added cut resistance, sidewall protection and exceptional traction.

**UM** US Standard

**Construction** RADIAL

**Machinery** OTR: Dozer, Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	195 A2

### Dimensions US Standard

Usa code	94046256
Overall Width (inch)	24.1
Overall Diameter (inch)	65.4
Static Loaded Radius (inch)	29.3
Rolling Circumference (inch)	192.2
Rim Rec	19.50/2.5
Rim Alt	19.50/2.5 IF
Star Rating	*
TRA Code	L5

### Load capacity (lbs)

mph / psi	58	62	65	69	73
5	22700	23400	24700	25400	26800

*publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*