

EARTHMAX SR 57 - Data Sheet



Description

EARTHMAX SR 57 is an All Steel radial tire specially engineered for loaders, dozers and utility vehicles operating in underground mines. The tire provides superior traction, stability and comfort on severe and rocky surfaces. The L-5 extra deep tread and the specially formulated UMS (underground mine service) compound provide a longer tread wear in addition to extraordinary resistance to rock cuts, and punctures.

UM

US Standard

Construction

RADIAL

Machinery

OTR: Dozer, Load Haul Dump (LHD), Loader

| SIZE | Version | USACode | TRA Code | Star R | LI/SS | RIM REC | RIM ALT | OW | OD | Type |
|------------|------------------------|----------|----------|--------|--------|-----------|---------|------|------|------|
| 10.00 R 15 | CUT RESISTANT COMPOUND | 94065615 | L5 | * | | 7.50 | 7.00 | 10.9 | 36.1 | TT |
| 7.50 R 15 | CUT RESISTANT COMPOUND | 94051687 | L5 | * | | 6.00 | 6.5 | 8.8 | 33.3 | TT |
| 8.25 R 15 | CUT RESISTANT COMPOUND | 94052783 | L5 | * | | 6.50 | 7.00 | 9.4 | 34.6 | TT |
| 12.00 R 20 | CUT RESISTANT COMPOUND | 94057160 | L5 | * | | 8.50 | | 12.5 | 46.5 | TT |
| 18.00 R 25 | CUT RESISTANT COMPOUND | 94063307 | L5 | ** | 204 A2 | 13.00/2.5 | | 20.3 | 65 | TL |

Printed on 03/10/2022 12:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..