

INDUSTRIAL RIB F3 - Data Sheet



Description

INDUSTRIAL RIB F3 is an agro-industrial rib-pattern tire designed for field and road transport as well as for soil tillage operations with implement machinery and trailers. This tire features an outstanding stubble-resistant compound making it suitable for the most critical operating conditions and ensuring a long tire life-cycle.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Implement Machinery, Trailer

SIZE	Version	TRA Code	L/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
11L - 15 SL	STANDARD	F3	117 A6	12	8 LB	10 LB	279	813	TL	E11-106R-004303
11L - 15 SL	STANDARD	F3	114 A6	10	8 LB	10 LB	279	813	TL	E11-106R-004302
11L - 15 SL	STUBBLE RESISTANT	F3	114 A6	10	8 LB	10 LB	279	813	TL	E11-106R-006914
11L - 15 SL	STUBBLE RESISTANT	F3	117 A6	12	8 LB	10 LB	279	813	TL	E11-106R-005311
11L - 16 SL	SPECIAL	F3	116 A6	10	W 8 L	8 LB ; 10 LB ; W 10 L	279	830	TL	E11-106R-004304
11L - 16 SL	STANDARD	F3	120 A6	12	W 8 L	8 LB ; 10 LB ; W 10 L	279	830	TL	E11-106R-004306
11L - 16 SL	STANDARD	F3	116 A6	10	W 8 L	8 LB ; 10 LB ; W 10 L	279	830	TL	E11-106R-004304

Printed on 19/10/2021 01:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..