

LP 450 - Technical Specifications



Description	LP 450 is a road-oriented tire for low platforms in transport applications. This high-speed tire provides significant fuel savings as well as an extended tire life-cycle.
UM	International Standard
Construction	BIAS
Machinery	Industrial: Low Platform Trailer

Version	STANDARD
Type	TL
Tyre Size	9 - 14.5

Dimensions International Standard

Ply Rating	14
Section Width (mm)	246
Overall Diameter (mm)	712
Static Loaded Radius (mm)	322
Rolling Circumference (mm)	2115
Rim Rec	7.00 MH

Load capacity (Kg)

km/h / bar	7.90
100 LS	1625
100 LD	1430

Printed on 20/10/2021 06:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..