



MULTIMAX MP 529 - Technical Specifications



Description

MULTIMAX MP 529 is a steel belted multi-purpose radial tire designed for telehandlers in industrial applications. Its tread design has been specially developed for hard surfaces. The strong sidewall and the larger footprint area ensure outstanding stability in lift mode. MULTIMAX MP 529 also features a strong puncture-resistant casing and is made of a special cut-and-chip-resistant compound providing extraordinary durability and a long service life.

UM

US Standard

Construction

RADIAL

Machinery

Industrial: Telehandler

| | |
|-----------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 340/80 R 18 |
| LI/SS | 143 A8/B |

Dimensions US Standard

| | |
|------------------------------|------------------------------------|
| Usa code | 94054305 |
| Section Width (inch) | 13.5 |
| Overall Diameter (inch) | 39.4 |
| Static Loaded Radius (inch) | 17.5 |
| Rolling Circumference (inch) | 118.4 |
| Rim Rec | 11 |
| Rim Alt | W 10 ; 11 SDC ; W 11 ; 12 ; 12 SDC |
| ECE | E11-106R-002972 |

Load capacity (lbs)

| mph / psi | 23 | 29 | 35 | 41 | 46 | 51 | 58 | 61 | 64 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|
| 30 | 2890 | 3430 | 3910 | 4450 | 4990 | 5360 | 6010 | - | - |
| 25 | 2890 | 3430 | 3910 | 4450 | 4990 | 5360 | 6010 | - | - |
| 20 | 3100 | 3670 | 4190 | 4770 | 5350 | 5730 | 6440 | - | - |
| 15 | 3210 | 3800 | 4340 | 4940 | 5540 | 5940 | 6670 | - | - |
| 5 Cyc. | 3530 | 4330 | 5100 | 5860 | 6680 | 7260 | 8210 | 8660 | 9020 |
| Static | 5400 | 6640 | 7810 | 8990 | 10230 | 11130 | 12590 | 13270 | 13820 |

Printed on 20/10/2021 05:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..