

MULTIMAX MP 569 - Technical Specifications



Description

The new tire MULTIMAX MP 569 is specifically designed for agro trucks. It is the innovative solution that enhances both tractor and truck performance features to meet the special needs of modern farming during several applications. Thanks to its All Steel casing, the tire stands out for its high speed capability and durability. The optimized tread pattern provides enhanced traction on field and great selfcleaning properties, together with an extremely comfortable drive on road and great stability. Not to mention that MULTIMAX MP 569 ensures significant savings in fuel consumption thanks to a low rolling resistance.

UM

US Standard

Construction

RADIAL

Machinery

Agriculture: Telehandler, Agro Truck
Industrial: Telehandler

Version	STANDARD
Type	TL
Tyre Size	445/65 R 22.5 (18 R 22.5)
LI/SS	169 J

Dimensions US Standard

Usa code	94067268
Overall Width (inch)	17.3
Overall Diameter (inch)	46.2
Static Loaded Radius (inch)	20.8
Rolling Circumference (inch)	140.1
Rim Rec	13.00
Rim Alt	14.00
ECE	E11-54R-0019094

Load capacity (lbs)

mph / psi	
62	130
	12800

Printed on 07/10/2022 05:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..