

## POWER TRAX HD (FL) - Technical Specifications



### Description

POWER TRAX HD is a premium bias-ply tire that is specially designed for forklift equipment in industrial applications. The deep tread, the extra thick sidewall and the tough casing provide exceptional durability minimizing the risk of punctures and accidental damages. The tire features excellent cut, chip and tear resistance suitable for rough and hard concrete surface. The specially designed rim guard ensures protection against flats and wheel damages in the rim flange area.

### UM

International Standard

### Construction

BIAS

### Machinery

Industrial: Forklift

|           |            |
|-----------|------------|
| Version   | IMPLEMENT  |
| Type      | TT         |
| Tyre Size | 10.00 - 20 |
| LI/SS     | 160 A8     |

### Dimensions International Standard

|                       |                 |
|-----------------------|-----------------|
| Ply Rating            | 16              |
| Section Width (mm)    | 285             |
| Overall Diameter (mm) | 1080            |
| Rim Rec               | 7.5             |
| Rim Alt               | 8.0             |
| ECE                   | E11-106R-003664 |

### Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 9.00 |
| 40         | 4500 |

*permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*