

POWER TRAX HD SMOOTH - Technical Specifications



Description

POWER TRAX HD SMOOTH is a bias-ply tire specially designed for port and underground mining operations. The special sidewall protection along with a solid tread prevents cut and puncture damages that are common in such demanding environments. When you need to move heavy-duty loads, Power Trax HD Smooth is your ideal partner.

UM

International Standard

Construction

BIAS

Machinery

Industrial: Container Handler, Forklift
OTR: Underground Mining Vehicle

Version	STANDARD
Type	TT
Tyre Size	12.00-20

Dimensions International Standard

Ply Rating	28
Section Width (mm)	320
Overall Diameter (mm)	1150
Rim Rec	8.50
Rim Alt	9.0

Load capacity (Kg)

km/h / bar	
25 LOAD WHEEL	9490
25 STEER WHEEL	7300
10 OTHER VEHICLES	9490
25 OTHER VEHICLES	7300
STATIC SIDE LOADER	11025

publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..