



## ***RIB 900 - Data Sheet***



*Description*

RIB 900 is suitable for transport, soil tillage and hay harvesting operations with trailers, implement machinery and balers. It offers great load capacity and a long tire life-cycle.

*UM*

International Standard

*Construction*

BIAS

*Machinery*

Agriculture: Baler, Hay Harvester, Implement Machinery, Trailer

| SIZE          | Version  | LI/SS FREE ROLLING | PR | RIM REC  | RIM ALT | SW  | OD  | SLR | RC   | Type | ECE            |
|---------------|----------|--------------------|----|----------|---------|-----|-----|-----|------|------|----------------|
| 400/60 - 15.5 | STANDARD | 139 A8             | 10 | AG 13.00 |         | 405 | 875 | 380 | 2564 | TL   |                |
| 400/60 - 15.5 | STANDARD | 145 A8             | 14 | AG 13.00 |         | 405 | 875 | 380 | 2564 | TL   | E4-106R-001551 |
| 400/60 - 15.5 | STANDARD | 147 A8             | 16 | AG 13.00 |         | 405 | 875 | 380 | 2564 | TL   | E4-106R-001548 |

Printed on 15/08/2022 11:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..