

ROCK GRIP L4 - Technical Specifications



Description

ROCK GRIP (L-4) is a bias-ply tire designed for wheel loader operations in severe loading service and on rough ground conditions. Its specially designed, cut-and-chip-resistant tread compound minimizes punctures thereby reducing machine downtime. The (L-4) tread depth provides an extended tire life-cycle.

UM

International Standard

Construction

BIAS

Machinery

Industrial: Dozer, Loader

Version	STANDARD
Type	TL
Tyre Size	14.00 - 25

Dimensions International Standard

Ply Rating	24
Overall Width (mm)	375
Overall Diameter (mm)	1410
Static Loaded Radius (mm)	649
Rolling Circumference (mm)	4173
Rim Rec	10.00/1.5
TRA Code	L4

Load capacity (Kg)

km/h / bar	8.50
10	9500

Printed on 03/10/2022 12:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..

