

SNOW RIDE - PLUS - Data Sheet



Description

SNOW RIDE - PLUS is particularly suitable for road applications in winter conditions. It features excellent traction and is ideal for ice and snow operations. Its specially designed tread pattern eliminates slippage risks.

UM

International Standard

Construction

BIAS

Machinery

Industrial: Loader

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
20.5 - 25	STANDARD	L2	16	17.00/2.0	17.00/1.7	525	1485	656	4370	TL
23.5 - 25	STANDARD	L2	16	19.50/2.5		600	1630	694	4765	TL

Printed on 26/09/2022 14:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..