

## ***SUPER TRAX HD - Technical Specifications***



### *Description*

SUPER TRAX HD has been specifically engineered for forklifts in heavy-duty material handling operations, including port and mining applications. The extra deep tread is made of a unique wear-resistant tread compound ensuring a longer service life. SUPER TRAX HD features a strong casing and a reinforced sidewall resulting in both excellent stability and maneuvering in lift mode. The specially designed rim guard provides protection against flats and wheel damage in the rim flange area.

### *UM*

International Standard

### *Construction*

BIAS

### *Machinery*

Industrial: Forklift

<i>Version</i>	STANDARD
<i>Type</i>	TT
<i>Tyre Size</i>	6.50 - 10

### *Dimensions International Standard*

<i>Ply Rating</i>	12
<i>Section Width (mm)</i>	195
<i>Overall Diameter (mm)</i>	600
<i>Static Loaded Radius (mm)</i>	282
<i>Rolling Circumference (mm)</i>	1838
<i>Rim Rec</i>	5.00 F
<i>Rim Alt</i>	5.50 F

## Load capacity (Kg)

km/h / bar	9.00
25 LOAD WHEEL	2145
25 STEER WHEEL	1650
10 OTHER VEHICLES	2145
25 OTHER VEHICLES	1650
STATIC SIDE LOADER	2490

Printed on 19/10/2021 02:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..