TR 173 - Data Sheet

Description

TR 173 is a tractor tire suitable for wet conditions and paddy fields. The special tread pattern provides outstanding self-cleaning properties in addition to reduced soil compaction thanks to a large contact area.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Tractor

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
8 - 18	STANDARD	R1W	94 A6	6	W 6	W 7 ; 5.50 F	200	841	392	2525		TT	E11-106R-006500
8.3 - 20	STANDARD	R1W	96 A6	6	W 7	W 6	211	890	418	2713		TT	E11-106R-006482
8.3 - 22	STANDARD	R1W	98 A6	6	W 7	W 6	211	940	443	2869		TT	E11-106R-006483
9.5 - 22	STANDARD	R1W	104 A6	6	W 8	W 7	241	997	472	3045		TT	E11-106R-006485
12.4 - 24	STANDARD	R1W	115 A6	6	W 11	W 9 ; W 10	315	1160	541	3509	550	TT	E11-106R-004480
8.3 - 24	STANDARD	R1W	100 A6	6	W 7	W 6	211	995	467	3009		TT	E11-106R-006484
9.5 - 24	STANDARD	R1W	106 A6	6	W 8	W 7	241	1047	493	3238		TT	E11-106R-006486
13.6 - 26	STANDARD	R1W	120 A6	6	W 12	W 11	345	1255	586	3786		TT	E11-106R-003555
14.9 - 28	STANDARD	R1W	130 A6	8	W 13	W 11 ; W 12	385	1367	631	4215		TT	E11-106R-006487
16.9 - 28	STANDARD	R1W	129 A6	6	W 15 L	W 14 L	445	1450	669	4454		TT	E11-106R-006488

Printed on 4/17/2024 9:55 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..