



## TR 390 IND - Technical Specifications

□

### Description

TR 390 IND is an industrial tire suitable for industrial trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

### UM

International Standard

### Construction

BIAS

### Machinery

Industrial: Compactor, Industrial Tractor, Trailer

|           |              |
|-----------|--------------|
| Version   | DUAL BEAD HD |
| Type      | TL           |
| Tyre Size | 28L - 26     |
| LI/SS     | 172 A6       |

### Dimensions International Standard

|                            |         |
|----------------------------|---------|
| Ply Rating                 | 20      |
| Section Width (mm)         | 714     |
| Overall Diameter (mm)      | 1560    |
| Static Loaded Radius (mm)  | 690     |
| Rolling Circumference (mm) | 4545    |
| Rim Rec                    | DW 25 B |
| Rim Alt                    | DW 23 B |
| TRA Code                   | R3      |

### Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 2.80 |
| 30         | 6300 |

*its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*