



TR 675 - Technical Specifications

□

Description

TR 675 is a bias tire specially designed for forestry applications. Its robust lug design provides excellent traction and self-cleaning, while the strong casing structure allows to carry heavy loads and its steel belts protect the tire from punctures and damages. TR 675 features a cut-resistant tread compound providing excellent cut-and-chip resistance even on difficult terrains under extreme conditions.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Forwarder

Version	STEEL BELTED
Type	TL
Tyre Size	540/65 - 28
LI/SS	155 A8/161 A2

Dimensions International Standard

Ply Rating	16
Section Width (mm)	530
Overall Diameter (mm)	1425
Static Loaded Radius (mm)	663
Rolling Circumference (mm)	4440
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E11-106R-005271
TRA Code	LS2

Load capacity (Kg)

km/h / bar

40

3.30

3875

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..