

AGRI GRIP - Technical Specifications



Description

AGRI GRIP is a tire for transport operations and particularly suitable for sugarcane trailers. AGRI GRIP has a strong casing providing high load capacity and particular cut-and-chip resistance. Its tread pattern has been designed for a longer service life.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Trailer

Version	DUAL BEAD
Type	TL
Tyre Size	23.1 - 26

Dimensions International Standard

Ply Rating	18
Overall Width (mm)	595
Overall Diameter (mm)	1560
Static Loaded Radius (mm)	708
Rolling Circumference (mm)	4658
Rim Rec	DW 20 B

Load capacity (Kg)

km/h / bar	2.60
30 FR LLV	5600

Printed on 4/25/2024 8:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..