

AGRI GRIP - Technical Specifications



Description

AGRI GRIP is a tire for transport operations and particularly suitable for sugarcane trailers. AGRI GRIP has a strong casing providing high load capacity and particular cut-and-chip resistance. Its tread pattern has been designed for a longer service life.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Trailer

| | |
|-----------|-----------|
| Version | DUAL BEAD |
| Type | TL |
| Tyre Size | 23.1 - 26 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94045747 |
| Ply Rating | 18 |
| Overall Width (inch) | 23.4 |
| Overall Diameter (inch) | 61.4 |
| Static Loaded Radius (inch) | 27.9 |
| Rolling Circumference (inch) | 183.4 |
| Rim Rec | DW 20 B |

Load capacity (lbs)

| | |
|-----------|-------|
| mph / psi | 38 |
| 20 FR LLV | 12350 |

Printed on 4/25/2024 4:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..