

## AGRIMAX ELOS - Technical Specifications



### Description

AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	480/70 R 34
LI/SS	155 A8/155 B

## Dimensions International Standard

Section Width (mm)	500
Overall Diameter (mm)	1605
Static Loaded Radius (mm)	733
Rolling Circumference (mm)	4868
SRI (mm)	750
Rim Rec	W 15 L
Rim Alt	W 16 L ; W 14 L
ECE	E11-106R-007532
TRA Code	R2

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	1515	1785	2055	2290	2560	2790	3065	3375	3645	3875
40	1515	1785	2055	2290	2560	2790	3065	3375	3645	3875
30	1620	1910	2200	2450	2740	2990	3280	3615	3905	4150
10 LT	2030	2390	2755	3070	3430	3745	4105	4520	4885	5195
10 HT	1620	1910	2200	2450	2740	2990	3280	3615	3905	4150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/14/2024 11:04 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..