

## AGRIMAX RT 600 - Technical Specifications

### Description

AGRIMAX RT 600 is the ideal tire for grassland, harvesting and spreading applications. Thanks to its large contact area, AGRIMAX RT 600 ensures an excellent pressure distribution on the land reducing damage on grassland and protecting your soil. Thanks to its round shoulder technology, the reinforced bead and increased number of lugs, it guarantees great stability and traction.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Harvester • Spreader • Tractor



Version	STANDARD
Type	TL
Tyre Size	800/65 R 32 (30.5L R 32)
LI/SS	181 A8/178 B

## Dimensions International Standard

Section Width (mm)	775
Overall Diameter (mm)	1820
Static Loaded Radius (mm)	823
Rolling Circumference (mm)	5558
SRI (mm)	875
Rim Rec	DW 27 B
Rim Alt	DH 27 B ; DW 25 B
ECE	E4-106R-001429

## Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	3175	3660	4485	4900	5385	5865	6350	6900	7500	-	-
40	3450	3975	4875	5325	5850	6375	6900	7500	8250	-	-
30	3695	4255	5220	5700	6260	6825	7385	8025	8830	-	-
10 LT	4625	5330	6535	7140	7840	8545	9250	10050	11055	-	-
10 HT	3695	4255	5220	5700	6260	6825	7385	8025	8830	-	-
10 Cyc	-	5655	7230	7960	9250	10140	11055	12025	12440	13000	14000

Printed on 3/22/2023 10:03 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..