

## AGRIMAX RT 657 - Technical Specifications



### Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	340/65 R 20
LI/SS	124 D/127 A8

## Dimensions US Standard

Usa code	94042005
Section Width (inch)	13.5
Overall Diameter (inch)	37.4
Static Loaded Radius (inch)	16.9
Rolling Circumference (inch)	113.9
Rim Rec	W 11
Rim Alt	W 10 ; W 12
ECE	E4-106R-001413
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	1660	1940	2230	2470	2720	2930	3250	3530
30	1740	2040	2340	2600	2850	3080	3420	3700
25	1820	2130	2440	2700	2980	3210	3550	3860
20	1910	2240	2560	2840	3130	3370	3740	4060
5 LT	2230	2600	2990	3320	3650	3940	4350	4730
5 HT	1910	2240	2560	2840	3130	3370	3740	4060

Printed on 4/12/2024 4:54 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..