

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	420/65 R 20
LI/SS	135 D/138 A8

Dimensions International Standard

Section Width (mm)	418
Overall Diameter (mm)	1054
Static Loaded Radius (mm)	468
Rolling Circumference (mm)	3162
SRI (mm)	500
Rim Rec	W 13
Rim Alt	W 11 ; W 12
ECE	E4-106R-001390
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1025	1200	1375	1530	1680	1810	2010	2180
50	1080	1260	1445	1605	1765	1905	2110	2290
40	1110	1300	1490	1655	1820	1960	2175	2360
30	1180	1385	1585	1760	1935	2085	2310	2510
10 LT	1375	1610	1845	2050	2255	2430	2695	2925
10 HT	1180	1385	1585	1760	1935	2085	2310	2510

Printed on 4/12/2024 5:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..