

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	420/65 R 28
LI/SS	135 D/138 A8

Dimensions International Standard

Section Width (mm)	418
Overall Diameter (mm)	1257
Static Loaded Radius (mm)	584
Rolling Circumference (mm)	3824
SRI (mm)	600
Rim Rec	W 13
Rim Alt	W 12 ; W 11
ECE	E11-106R-002974
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1025	1180	1355	1530	1705	1875	2030	2180
50	1080	1240	1420	1605	1790	1970	2130	2290
40	1110	1275	1465	1655	1845	2030	2195	2360
30	1180	1360	1560	1760	1960	2160	2335	2510
10 LT	1375	1580	1815	2050	2285	2520	2725	2925
10 HT	1180	1360	1560	1760	1960	2160	2335	2510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 7:05 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..