

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	440/65 R 28
LI/SS	138 D/141 A8

Dimensions US Standard

Usa code	94029143
Section Width (inch)	17.4
Overall Diameter (inch)	50.5
Static Loaded Radius (inch)	23.2
Rolling Circumference (inch)	154.6
Rim Rec	W 14 L
Rim Alt	W 13 ; W 15 L
ECE	E4-106R-000767
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	2500	2920	3280	3650	4010	4320	4790	5200
30	2630	3060	3450	3840	4210	4540	5040	5470
25	2730	3190	3580	3980	4380	4720	5220	5680
20	2880	3360	3780	4200	4620	4970	5510	5990
5 LT	3350	3910	4400	4890	5380	5800	6430	6980
5 HT	2880	3360	3780	4200	4620	4970	5510	5990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 2:35 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..