

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	480/65 R 24
LI/SS	140 D/143 A8

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1234
Static Loaded Radius (mm)	562
Rolling Circumference (mm)	3730
SRI (mm)	600
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E4-106R-000617
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1200	1400	1575	1750	1925	2075	2300	2500
50	1260	1470	1655	1840	2025	2180	2415	2625
40	1310	1530	1720	1910	2100	2265	2510	2725
30	1380	1610	1815	2015	2215	2390	2645	2875
10 LT	1610	1880	2115	2345	2580	2785	3085	3350
10 HT	1380	1610	1815	2015	2215	2390	2645	2875

Printed on 3/20/2024 11:10 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..