AGRIMAX RT 657 - Technical Specifications

Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

US Standard

Construction

RADIAL

Machinery

Agriculture: Tractor • Vineyard Harvester

Version	SPECIAL
Type	TL
Tyre Size	540/65 R 34
LI/SS	152 D/155 A8

Dimensions US Standard

Usa code	94062645
TMPH	1
Section Width (inch)	20.9
Overall Diameter (inch)	61.7
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	186.7
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E4-106R-000652
TRA Code	R1W

Load capacity (lbs)

mph / psi	90	12	15	17	20	23	29	35
40	3760	4390	4940	5480	6030	6500	7210	7850
30	3960	4610	5180	5760	6340	6830	7570	8220
25	4100	4780	5390	5990	6580	7100	7860	8540
20	4330	5050	5680	6300	6940	7480	8290	9010
5 LT	5040	5890	6610	7350	8090	8720	9660	10490
5 HT	4330	5050	5680	6300	6940	7480	8290	9010

Printed on 4/26/2024 12:08 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..