

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	540/65 R 38
LI/SS	153 D/156 A8

Dimensions International Standard

Section Width (mm)	530
Overall Diameter (mm)	1667
Static Loaded Radius (mm)	760
Rolling Circumference (mm)	5059
SRI (mm)	800
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E4-106R-000589
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1755	2045	2300	2555	2815	3030	3360	3650
50	1845	2150	2420	2685	2955	3185	3530	3835
40	1920	2240	2520	2800	3080	3320	3680	4000
30	2020	2355	2650	2940	3235	3490	3865	4200
10 LT	2350	2745	3085	3430	3770	4065	4505	4895
10 HT	2020	2355	2650	2940	3235	3490	3865	4200

Printed on 4/12/2024 5:29 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..