

## AGRIMAX RT 657 - Technical Specifications



### Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	600/65 R 30
LI/SS	155 D/158 A8

Dimensions US Standard

Usa code	94032310
Section Width (inch)	24.1
Overall Diameter (inch)	60.7
Static Loaded Radius (inch)	27.4
Rolling Circumference (inch)	181.5
Rim Rec	DW 20 B
Rim Alt	W 18 L
ECE	E4-106R-001825
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	4100	4780	5390	5990	6580	7100	7860	8540
30	4310	5030	5650	6280	6910	7450	8260	8970
25	4500	5250	5910	6560	7220	7780	8620	9370
20	4730	5510	6190	6890	7570	8170	9050	9830
5 LT	5500	6420	7220	8020	8830	9510	10540	11450
5 HT	4730	5510	6190	6890	7570	8170	9050	9830

Printed on 4/24/2024 11:37 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..