

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

US Standard

Construction



Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Туре	TL
Tyre Size	260/70 R 16
LI/SS	109 A8/B

Dimensions US Standard

Usa code	94021888
Section Width (inch)	10.2
Overall Diameter (inch)	30.3
Static Loaded Radius (inch)	13.6
Rolling Circumference (inch)	89.9
Rim Rec	W 8
Rim Alt	W 8 L ; W 9 L
ECE	E4-106R-000610
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	1070	1230	1410	1600	1770	1960	2120	2270
25	1070	1230	1410	1600	1770	1960	2120	2270
20	1150	1320	1520	1710	1910	2110	2270	2440
5 LT	1430	1650	1900	2140	2380	2620	2830	3040
5 HT	1150	1320	1520	1710	1910	2110	2270	2440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 9:13 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..