

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steelbelted technology.

UM

US Standard

Construction

RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

| Version | SPECIAL |
|-----------|-------------|
| Туре | TL |
| Tyre Size | 480/70 R 34 |
| LI/SS | 155 D |

Dimensions US Standard

| Usa code | 94063284 |
|------------------------------|-----------------|
| Section Width (inch) | 18.9 |
| Overall Diameter (inch) | 62.2 |
| Static Loaded Radius (inch) | 28.7 |
| Rolling Circumference (inch) | 188.5 |
| Rim Rec | W 15 L |
| Rim Alt | W 14 L ; W 16 L |
| ECE | E11-106R-005834 |
| TRA Code | R1W |

Load capacity (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 47 |
|-----------|------|------|------|------|------|------|------|------|-------|-------|
| 40 | 3340 | 3940 | 4530 | 5050 | 5640 | 6150 | 6760 | 7260 | 7950 | 8540 |
| 30 | 3510 | 4130 | 4760 | 5300 | 5930 | 6470 | 7100 | 7630 | 8360 | 8970 |
| 25 | 3660 | 4310 | 4960 | 5520 | 6180 | 6750 | 7400 | 7960 | 8710 | 9360 |
| 20 | 3840 | 4530 | 5210 | 5810 | 6490 | 7090 | 7770 | 8370 | 9150 | 9830 |
| 5 LT | 4480 | 5270 | 6070 | 6770 | 7560 | 8260 | 9050 | 9740 | 10660 | 11450 |
| 5 HT | 3840 | 4530 | 5210 | 5810 | 6490 | 7090 | 7770 | 8370 | 9150 | 9830 |

Printed on 4/19/2024 12:03 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..