

## AGRIMAX RT 855 - Technical Specifications



### Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

### UM

International Standard

### Construction



RADIAL

### Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	420/85 R 34 (16.9 R 34)
LI/SS	147 A8/B

## Dimensions International Standard

Section Width (mm)	438
Overall Diameter (mm)	1578
Static Loaded Radius (mm)	728
Rolling Circumference (mm)	4782
SRI (mm)	750
Rim Rec	W 15 L
Rim Alt	W 13 ; W 14 L
ECE	E11-106R-005179
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	1450	1665	1910	2155	2400	2645	2895	3075
40	1450	1665	1910	2155	2400	2645	2895	3075
30	1550	1780	2045	2310	2575	2835	3100	3295
10 LT	1940	2230	2560	2890	3220	3550	3880	4125
10 HT	1550	1780	2045	2310	2575	2835	3100	3595

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 6:56 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..