

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	460/85 R 30 (18.4 R 30)
LI/SS	156 A8/B

Dimensions US Standard

Usa code	94047765
Section Width (inch)	18.7
Overall Diameter (inch)	60.8
Static Loaded Radius (inch)	26.8
Rolling Circumference (inch)	179.6
Rim Rec	W 16 L
Rim Alt	W 14 L ; W 15 L
ECE	E11-106R-007812
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46
30	3440	4060	4670	5200	5820	6350	6970	7500	8200	8820
25	3440	4060	4670	5200	5820	6350	6970	7500	8200	8820
20	3680	4340	5000	5580	6230	6800	7460	8020	8780	9440
5 LT	4620	5450	6270	6980	7800	8510	9340	10050	10990	11820
5 HT	3680	4340	5000	5580	6230	6800	7460	8020	8780	9440

Printed on 4/23/2024 2:14 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..