

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	SPECIAL
Type	TL
Tyre Size	520/85 R 38 (20.8 R 38)
LI/SS	155 A8/B

Dimensions International Standard

Section Width (mm)	516
Overall Diameter (mm)	1849
Static Loaded Radius (mm)	813
Rolling Circumference (mm)	5466
SRI (mm)	875
Rim Rec	DW 16 L
Rim Alt	DW 18 L ; DD 16 L
ECE	E4-106R-000601
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	2170	2560	2910	3255	3565	3875
40	2170	2560	2910	3255	3565	3875
30	2325	2740	3115	3490	3820	4150
10 LT	2910	3430	3900	4365	4780	5195
10 HT	2325	2740	3115	3490	3820	4150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 1:44 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..