

# AGRIMAX RT 945 - Technical Specifications



## Description

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Sprayer • Tractor

Version	STANDARD
Type	TL
Tyre Size	320/90 R 50 (12.4 R 50)
LI/SS	150 A8/B

## Dimensions US Standard

Usa code	94037612
Section Width (inch)	12.6
Overall Diameter (inch)	72.7
Static Loaded Radius (inch)	34.4
Rolling Circumference (inch)	221.2
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E4-106R-000787
TRA Code	R1W

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58
30	3110	4070	4950	5400	5760	6280	6800	7400	-
25	3110	4070	4950	5400	5760	6280	6800	7400	-
20	3330	4350	5300	5780	6170	6720	7270	7900	-
5	4320	5650	6880	7540	7980	8750	9530	10310	11080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/8/2024 7:46 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..