

AGRIMAX RT 945 - Technical Specifications



Description

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor

Version	STANDARD
Type	TL
Tyre Size	320/90 R 54 (12.4 R 54)
LI/SS	156 A8/B

Dimensions US Standard

Usa code	94037094
Section Width (inch)	12.6
Overall Diameter (inch)	76.7
Static Loaded Radius (inch)	36.6
Rolling Circumference (inch)	237
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E11-106R-003474
TRA Code	R1W

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64	70
30	3310	4270	5160	5720	6040	6600	7160	7650	8050	8820	-
25	3310	4270	5160	5720	6040	6600	7160	7650	8050	8820	-
20	3540	4570	5520	6130	6470	7080	7670	8190	8620	9440	-
5	-	4100	5160	6350	7540	8730	8990	10050	11110	12170	13230

Printed on 4/18/2024 2:05 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..